

NOTES:

- 1. ON MEDIANS LESS THAN 14 FEET WIDE, REPLACE MAINTENANCE BAND WITH 18 INCH MINIMUM WIDTH PLANTING OF WALKABLE GROUNDCOVER.
- 2. IF CONRETE, INSTALL 'DEEP JOINTS' TO MATCH CURB & GUTTER DEEP JOINTS. SEE ENGINEERING STANDARD DETAIL 8 FOR DEFINITION OF 'DEEP JOINT.'
- 3. IF PAVERS ARE TO BE SET ADJACENT TO AN EXISTING TREE HAND EXCAVATE ALL AREAS WITHIN TREE DRIPLINE. SEE LSD-9 FOR TREE PRESERVATION NOTES.
- 4. PAVERS TO BE: 6 X 9 X 3 1/8 CALSTONE PERMEABLE PAVING UNITS, COLOR: RUSTIC YELLOW STONE, UNLESS APPROVED BY THE CITY LANDSCAPE ARCHITECT.

			CITY OF FREMONT STANDARD DETAILS			DATE APPROVED BY CITY COUNCIL 12/13/11 RESOLUTION NO. 2006-31		
APPR	Council Revision	n 12/13/11 DATE	CITY STANDARD				Nam Hughen	
REVISIONS			MAINTENANCE BAND				CITY ENGINEER	
FILE NO.			= 1'-0"	DRAWN PM/MM	CHECKED RER	DEC. 2011	DWG NO. LSD-8	1 of 1